



SWYPE 2.0 HT

Sram SX Eagle 12-speed / Bosch Performance Line CX / 625Wh

Article	Inch	Frame size	Color
122320541	29"	Unisex, 38 cm	black glossy
122320542	29"	Unisex, 42 cm	black glossy
122320543	29"	Unisex, 46 cm	black glossy
122320544	29"	Unisex, 50 cm	black glossy

Drive System

Motor

Bosch Performance Line CX, BES3

36 Volt, mid-engine

Output power 250 Watt

Display

Intuvia 100

Battery

Bosch frame battery fully-integrated

Energy content: 625 Wh

Voltage: 36 Volt

Capacity: 16.7 Ah

Technical changes and changes in equipment reserved, color deviations possible.

General	Frame	Aluminium 6061, Bosch BES3 fully integrated, Boost 12 x 148 mm
	Head set	Acros AZF-668-ICR, tapered, with cable integration
	Fork	Suntour XCM34, Boost, 120 mm suspension travel with lockout function
	Shifting System	Sram SX Eagle , 12-speed
	Derailleur	---
	Brakes	Magura MT Trail 4 pistons (front 203 mm / rear 203 mm)
	Headlight	N/V, N/V LUX
	Rear light	---
	Carrier	---
	Saddle	Selle Royal Vivo E-MTB
	Seat post	Humpert Ergotec Atar, patent, 31.6 mm, 300 mm
	Pedals	Marwi SP-450 Flat Pedal, black
	Kickstand	---
	Chainguard	Herrmans chain guard
	Mudguard	---
	Other	max load 120 kg, light cable already installed in the frame
	Weight	23.5 kg
	Stem	Promax DA-205, 70 mm, 31.8 mm
	Handlebars	Promax Riser Bar HB-3188, 740 mm, 31.8 mm
	Grips	Ergon GA30, with clamp
	Shift lever	Sram SX Eagle, 12-speed, Single Click
	Brake lever	Magura MT Thirty
	Tires	Schwalbe Smart Sam, 65-622, Classic Skin
	Rims	Schürmann Craft 35 , 29", 32 holes
	Spokes	2.0 mm, black
	Front Hub	Sonos, Boost, 15 x 110 mm, 32 holes, 6-holes
	Rear Hub	Sonos, Boost, 12 x 148 mm, 32 holes, 6-holes
	Sprocket	Sram PG-1210 Eagle, 12-speed, 11-50 teeth
	Chain	Sram Eagle
	Inner bearing	---
	Bottom bracket	Miranda Aluminium, 170 mm, KMC chain ring 38 teeth, with chain guard
	Gear ratio (f:r)	38 teeth : 11-50 teeth