



SWYPE 2.0 FS Equipped

Sram SX Eagle 12-speed / Bosch Performance Line CX / 625Wh

Article	Inch	Frame size	Color
122320561	27.5"	Unisex, 39 cm	black glossy
122320562	27.5"	Unisex, 42 cm	black glossy
122320563	27.5"	Unisex, 45 cm	black glossy
122320564	27.5"	Unisex, 48 cm	black glossy

Drive System

Motor

Bosch Performance Line CX, BES3

36 Volt, mid-engine

Output power 250 Watt

Display

Intuvia 100

Battery

Bosch frame battery fully-integrated

Energy content: 625 Wh

Voltage: 36 Volt

Capacity: 16.7 Ah

Technical changes and changes in equipment reserved, color deviations possible.

General	Frame	fully integrated, Aluminium 6061, Boost 12 x 148 mm, Travel 140 mm
	Head set	Acros AZF-668-ICR, tapered, with cable integration
	Fork	Suntour XCR34, Boost, 140 mm suspension travel with lockout function
	Shifting System	Sram SX Eagle, 12-speed
	Derailleur	---
	Brakes	Magura MT5 4 pistons (front 203 mm / rear 203 mm)
	Headlight	Spanninga Axendo 40, 40 LUX
	Rear light	SKS, Infinity
	Carrier	SKS Infinity GT4, with spring flap
	Saddle	Selle Italia Model Y
	Seat post	Limotec A1, dropper with remote, 31.6 mm
	Pedals	Marwi SP-450 Flat Pedal, black
	Kickstand	---
	Chainguard	chain guide
	Mudguard	SKS A65R, plastic
	Other	max load 120 kg
	Weight	26.5 kg
Cockpit		
	Stem	Promax DA-230, 80 mm, 31.8 mm, with headlight holder
	Handlebars	Humpert Ergotec Low Riser Bar, 740 mm, 31.8 mm, Level 6+
	Grips	Ergon GA30, with clamp
	Shift lever	Sram SX Eagle, 12-speed, Single Click
	Brake lever	Magura MT Thirty
Wheels/Tires/Drivetrain		
	Tires	Schwalbe Smart Sam, 65-584
	Rims	Schürmann Craft 35, 27.5", 32 holes
	Spokes	2.0 mm, black
	Front Hub	Sonos, Boost, 15 x 110 mm, 32 holes, 6-holes
	Rear Hub	Sonos, Boost, 12 x 148 mm, 32 holes, 6-holes
	Sprocket	Sram PG-1210 Eagle, 12-speed, 11-50 teeth
	Chain	Sram Eagle
	Inner bearing	---
	Bottom bracket	Miranda Aluminium, 165 mm, Sram Eagle chain ring 34 teeth, Narrow Wide
	Gear ratio (f:r)	34 teeth : 11-50 teeth