



Raise RT5 Sport

Shimano Alivio 24-speed / Disc

Article	Inch	Frame size	Color
122320731	28"	Gents, 50 cm	anthracite matt
122320732	28"	Gents, 55 cm	anthracite matt
122320733	28"	Gents, 60 cm	anthracite matt
122320735	28"	Ladies, 45 cm	anthracite matt
122320736	28"	Ladies, 50 cm	anthracite matt
122320737	28"	Ladies, 55 cm	anthracite matt
122320740	28"	Wave, 45 cm	anthracite matt
122320741	28"	Wave, 50 cm	anthracite matt
122320742	28"	Wave, 55 cm	anthracite matt
122320751	28"	Gents, 50 cm	petrol matt
122320752	28"	Gents, 55 cm	petrol matt
122320753	28"	Gents, 60 cm	petrol matt
122320760	28"	Wave, 45 cm	beige glänzend
122320761	28"	Wave, 50 cm	beige glänzend
122320762	28"	Wave, 55 cm	beige glänzend

Technical changes and changes in equipment reserved, color deviations possible.

General	Frame	Aluminium 6061, 28" Trekking
	Head set	FSA, 1 1/8", a-head, semi integrated
	Fork	Suntour NEX
	Shifting System	Shimano Alivio RD-T4000, 8-speed
	Derailleur	Shimano Altus FD-M313, 3-speed
	Brakes	JAK Y-2 (front 160 mm / rear 160 mm)
	Headlight	Jing Yi LED plastic, 70 LUX
	Rear light	Trelock, LS 655
	Carrier	strutless, with spring flap
	Saddle	Selle Royal Rio
	Seat post	Humpert Ergotec Atar, patent, 27,2 mm, 300 mm
	Pedals	Marwi SP-823, black
	Kickstand	0688, rear kickstand
	Chainguard	Horn Catena 16
	Mudguard	SKS, plastic
	Other	max load 140 kg
	Weight	17.6 kg
Cockpit	Stem	a-head, angle adjustable, Aluminium 31.8mm
	Handlebars	Humpert Low Riser, 620 mm
	Grips	Hualong HL-G234 Ergo, with clamp
	Shift lever	Shimano Altus RS-315, 3-/8-speed
	Brake lever	Shimano Altus, 3-finger brake lever
	Shift lever	Shimano Altus RS-315, 3-/8-speed
Wheels/Tires/Drivetrain	Tires	Schwalbe Marathon Efficiency, 40-622, reflex
	Rims	Schürmann YAK19 Disc Aluminium hollow section, 36 holes
	Spokes	2.0 mm, black
	Front Hub	Shimano DH-3D37, hub dynamo, Centerlock, 36 holes
	Rear Hub	Shimano FH-TX505, Centerlock, 36 holes
	Sprocket	Shimano CS-HG200, 8-speed, 12-32 teeth
	Chain	KMC Z-51
	Inner bearing	Thun Topaz
Wheels/Tires/Drivetrain	Bottom bracket	Shimano TY-501, 170 mm, 48/38/28 teeth
	Gear ratio (f:r)	48/38/28 teeth : 12-32 teeth