



Vitality Eco 8+

Shimano Nexus 5-speed coaster brake / Bosch Performance Line / 625Wh / Disc / Gates

Article	Inch	Frame size	Color
122520061	28"	Wave, 50 cm	silver matt
122520062	28"	Wave, 55 cm	silver matt
122520063	28"	Wave, 60 cm	silver matt

Drive System

Motor

Bosch Performance Line, BES3

36 Volt, Mid-engine

Output power 250 Watt

Display

Intuvia 100

Battery

Bosch Frame battery fully integrated

Energy content: 625 Wh

Voltage: 36 Volt

Capacity: 16.7 Ah

Technical changes and changes in equipment reserved, color deviations possible.

General	
Frame	Aluminum 6061, Bosch fully integrated
Head set	Acros AZX-743F, tapered
Fork	Suntour Mobie25, with Lockout-Funktion
Shifting System	Shimano Nexus 5-speed coaster brake
Derailleur	---
Brakes	Shimano Deore BR-MT420/410, 4-/2-Kolben (front 180 mm / rear 180 mm)
Headlight	Herrmans MR4, 40 LUX
Rear light	Trelock, LS 654, with brake light function including standinglight
Carrier	Kreidler Basic Tour 2.0, strutless, with spring flap, compatible with Racktime Snap-It 2.0 System
Saddle	Selle Royal Essenza
Seat post	Humpert Ergotec Skalar, patent, 27.2 mm, 400 mm, Safety Level 6
Pedals	VP-617
Kickstand	Velo Rex, Rear stand
Chainguard	SKS Chainblade-E
Mudguard	SKS A53, plastic
Other	max. load 170 kg
Weight	27.7 kg
Cockpit	
Stem	Humpert Ergotec Swell RE, angle adjustable, Safety Level 6
Handlebars	Humpert Ergotec Ergo Plus L, Aluminium, 660 mm, safety level 6
Grips	Herrmans DD37, with Screw clamp
Shift lever	Shimano Nexus, twist shifter
Brake lever	Shimano Deore BL-MT402
Wheels/Tires/Drivetrain	
Tires	Schwalbe Marathon Plus, 47-622, reflex
Rims	Ryde Andra 40 Disc Aluminium Double Wall Alloy Rim, 36 holes
Spokes	ED Niro 2,34 mm
Front Hub	Shimano Alivio HB-MT400, 15 x 100 mm, Centerlock, 36 holes
Rear Hub	Shimano Nexus 5-speed SG-C7002-5CD, Centerlock, 36 holes, coaster brake
Sprocket	Gates CDX Drive belt, 32 teeth
Chain	Gates CDX-Drive belt
Inner bearing	---
Bottom bracket	Miranda Aluminium, 170 mm, 46 teeth
Gear ratio (f:r)	46 teeth : 32 teeth